



# Sopro ADS 630

## Waterproofing kit

Waterproofing kit with fully co-ordinated set containing all products needed for installation of waterproofing systems below tiling.



- Ready-to-use products
- Economical system solution
- Straightforward application
- Co-ordinated system components
- Particularly suitable for bathrooms and showers
- Including application guidance
- DGNB (German Sustainable Building Council): top quality level 4<sup>1)</sup>




Sopro GD 749 is an easily workable, rapid-drying, highly concentrated, solvent-free synthetic resin primer for pretreatment of high- or variable-suction substrates, e.g. cement screeds, calcium sulphate screeds, board subfloors, gypsum plasterboard, gypsum fibreboard, lime/cement render and gypsum plasterwork.

1 kg bottle



Sopro FDF flexible sealing compound is a highly elastic, crack-bridging, solvent-free, one-component liquid polymer waterproof coating for interiors, specifically domestic and commercial bathrooms, showers, washrooms and sanitary facilities. Ready-to-use Sopro FDF is simply applied by roller.

5 kg bucket



Sopro DMW 090 sealing collars for walls are used in installation of waterproofing systems for reliable sealing of 1/2" pipe penetrations below tiling.

Nr 2/size: approx. 120 x 120 mm



Sopro DB 438 is an expansible, nonwoven-backed, high-performance sealing tape for trouble-free, flexible bridging and waterproofing of perimeter and movement joints below tiling. Easy bedding of sealing tape due to flexible expansion zone.

5 m roll (120 mm wide)



Universal roller is ideal for application of Sopro GD 749 primer and Sopro FDF flexible sealing compound.

Pile height 12 mm, width 15 cm



Application guidance presents full explanations and step-by-step details of workmanship for all operations from waterproofing to tile grouting.

Shelf life

Approx. 24 months, subject to storage in cool, dry conditions in original unopened containers. Protect from frost.

<sup>1)</sup> Based on DGNB (German Sustainable Building Council) criterion "ENV1.2 Local Environmental Impact" (2015 version).

bringing european innovation

# smet

FOR MORE INFORMATION CONTACT: **Smet Building Products Ltd**

93A Belfast Road | Newry | BT34 1QH | Northern Ireland

T: +44 (0) 28 3026 6833 | F: +44 (0) 28 3026 7619

E: [info@smetbuildingproducts.com](mailto:info@smetbuildingproducts.com)

[www.smetbuildingproducts.com](http://www.smetbuildingproducts.com) or [www.smet.ie](http://www.smet.ie)



The information, and, in particular, the recommendations relating to the application and end-use of SMET distributed products, are given in good faith based on SMET's current knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance with the manufacturer's recommendations. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The user of the product must test the product's suitability for the intended application and purpose. The manufacturer reserves the right to change the properties of its products. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local Product Data Sheet for the product concerned, copies of which will be supplied on request.