







CE marking

|   |   |
|---|---|
|    | <br><b>Sopro Bauchemie GmbH</b><br>Biebricher Straße 74 – 65203 Wiesbaden (Germany)<br>www.sopro.com |
| 10<br>CPR-DE3/0678.2.eng<br>EN 13813:2002 CT-C25-F5-A12<br>Sopro Rapidur® FE 678<br>Cementitious screed material for internal use |   |
| Reaction to fire  | Class A1 <sub>n</sub>   |
| Release of corrosive substances   | CT  |
| Water permeability  | NPD   |
| Water vapour permeability   | NPD   |
| Compressive strength  | C25   |
| Flexural strength   | F5  |
| Wear resistance   | A12   |
| Sound insulation  | NPD   |
| Sound absorption  | NPD   |
| Thermal resistance  | NPD   |
| Chemical resistance   | NPD   |
| Release of dangerous substances   | see SDS   |

LRPD/LRCS/DL/APP/LR/LWRWBSL/LRIGWLEWBR/EMRCWEE/NR  
 SLRWSR/BSMVR/SLPQ/LRLB/WWPP/LRSD/LR  
 PDHEW/DVRCVLR/DRLG/RP/LLWRLWAG/DLSRADELLWDLRWR/LRLS  
 D/RHEW/PWLLRP/LRRPD/WAPP/LRRPBW/RBWB/PVW/WBR/LWELLR  
 WWSL/LRBSR/WWR/BSWLRLWSR/BSLW/DWRVLG/LWEE  
 BVEWRRW/RW/RWRW/LW/RB/RWRBR/BSLREEH  
 SLEW