PRODUCT DATA SHEET FIBERGLASS MESH SGG22 UNIVERSAL Baustoffe

Item number: 1310-050 / 1311-050

Square dimension: 10 x 10 mm **Width:** 100 cm

Colour: 1310-050 white / 1311-050 blue

Packaging unit: RM/rolls rolls/pallet

Rolls 50 25



TECHNICAL DATA:

Material:

Warp: E-glass Shot: E-glass

Thread density: (10 cm)

Warp: 10 turner strings Shot: 10 weft threads

Treated fabric weight: 145 g/m² Loss of ignition: 25 %

Characteristics: alkaliresistant, obstructing yarn drifting

Tensile strength per 5 cm:

STATE OF DELIVERY: MEASURED VALUE:

Tensile strength warp (N/5 cm) 1945 N Tensile strength shot (N/5 cm) 2210 N

28 DAYS STORAGE TO 5 % SODIUM HYDROXIDE:

Tensile strength warp (N/5 cm) 1265 N Tensile strength shot (N/5 cm) 1195 N

Made in Europe

The information, and, in particular, the recommendations relating to the application and end-use of SMET distributed products, are given in good faith based on SMET's current knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance with the manufacturer's recommendations. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The user of the product must test the product's suitability for the intended application and purpose. The manufacturer reserves the right to change the properties of its products. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local Product Data Sheet for the product





