



Sopro FH 867

Paving grout cleaning aid



High-alkaline liquid in aqueous solution used for temporary water-repellent treatment of absorbent concrete and natural stone paving units/coverings.

- Facilitates washing down and removal of grouts
- For brush and spray application
- Economical in use
- For walls and floors
- For indoor and outdoor use

Use

For impregnation of absorbent concrete and natural stone paving units/coverings to facilitate removal of cementitious and resinous paving grouts. For indoor and outdoor use.

Colour

Clear, colourless

Drying time

Allow at least 2 hours drying time and ensure that Sopro FH 867 has properly dried prior to grouting.

pH value

Approx. 12

Application temperature

Between +5 °C and max. +25 °C

Coverage

5–15 m²/ltr

Shelf life

Approx. 2 years, subject to storage in original unopened containers; use up opened containers as promptly as possible.

Packaging

10 ltr canister
5 ltr canister
1 ltr bottle (only available in box with Nr 4)

Properties

Sopro FH 867 is a high-alkaline, aqueous material used for temporary water-repellent treatment of absorbent paving units. Treatment with Sopro FH 867 facilitates grouting and subsequent cleaning of surface.

Application

Apply undiluted Sopro FH 867 uniformly to clean, surface-dry covering using roller or broad brush. Avoid irregularities in coat as these may lead to discoloration. Spray application is recommended for high-suction substrates. Apply only as much material as can be taken up by covering. With polished and low-suction coverings, remove surplus material after 10 minutes. Do not allow surplus material to dry on surface.

Allow at least 2 hours drying time and ensure that Sopro FH 867 has properly dried prior to grouting. **Trial laying of sample area is strongly recommended to confirm suitability of product.**

Tools/tool cleaning

Roller, brush, spray equipment; wash tools with water immediately after use.

Please note

Due to product-specific properties, non-uniform or overly thick application may result in irreversible staining and greying of surface.

Protect alkali-sensitive surfaces, e.g. wood, linoleum, glass etc. Immediately wipe off splashed/spattered material.

Disposal

Disposal with wastewater is permissible subject to dilution. Container is made from eco-friendly polyethylene (PE) and is recyclable. Clean, fully emptied containers may be disposed of via recycling collection system. WGK (German Water Hazard Class) 1 to VwVwS (German Administrative Regulations on the Classification of Substances Hazardous to Waters) of 17.5.1999.

Safety precautions

Labelling in accordance with Regulation (EC) No 1272/2008 (CLP)

GHS05

Signal word: Danger

Contains potassium methyl silicates.

Hazard statements: H314 Causes severe skin burns and eye damage.

Precautionary statements: P102 Keep out of reach of children. P280 Wear protective gloves/protective clothing/eye protection/face protection. P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P310 Immediately call a POISON CENTER or doctor. P332+P313 If skin irritation occurs: Get medical advice/attention. P405 Store locked up. P501 Dispose of contents/container in accordance with local regulations.

bringing european innovation

smet

FOR MORE INFORMATION CONTACT:

Smet Building Products Ltd | 93A Belfast Road | Newry | BT34 1QH | Northern Ireland
T: +44 (0) 28 3026 6833 | F: +44 (0) 28 3026 7619 | E: info@smetbuildingproducts.com

www.smetbuildingproducts.com or www.smet.ie



The information, and, in particular, the recommendations relating to the application and end-use of SMET distributed products, are given in good faith based on SMET's current knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance with the manufacturer's recommendations. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The user of the product must test the product's suitability for the intended application and purpose. The manufacturer reserves the right to change the properties of its products. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local Product Data Sheet for the product concerned, copies of which will be supplied on request.