

ProofBase

Product Data Sheet
Feb 2019

Universal Acrylic Primer



ProofBase Acrylic Primer is a universal, breathable primer that completes the ideal substrate preparation before the application of ProofTherm Insulating Render or Plaster.

ProofBase controls suction and provides an ideal adhesive key for optimum results in all rendering jobs. Its vapour permeable formulation allows the substrate to breathe and works in conjunction with ProofTherm Insulating Render/Plaster to maintain a healthy, damp free internal environment.

Vapour Permeable Acrylic Primer



ProofBase

Product Data

Description

ProofBase is a universal, acrylic primer which is used to treat substrates before the application of ProofTherm Insulating Render or Plaster. It is sold in ready to apply 15l tubs. One tub will cover approximately 125m².

Properties

- Highly vapour permeable
- Hydrophobic acrylic formulation
- Easily applied using a roller or brush
- Rapid drying

Composition

- Water
- Acrylic Polymers
- Silica aggregates

Storage

18 months, stored in protected, dry conditions.

Disposal Considerations

Regional legislation (waste): Disposal must be done according to official regulations. Waste Management Regulation published in the Official Journal numbered 29314 on April 2, 2015. Regulation on Incineration of Waste Materials published in the Official Journal numbered 27721 on October 6, 2010. Waste treatment methods: Dispose of contents/container in accordance with licensed collector's sorting instructions. Do not remove as household garbage. Sewage disposal recommendations: Disposal must be done according to official regulations. Additional information: Empty containers should be taken for recycling, recovery or waste in accordance with local regulation.

Safety

All standard precautions for the handling of construction materials/chemicals must be taken. See ProofShield safety data sheet for detailed info. Classification according to Regulation (EC) No 1272/2008. Not classified.



ProofShield

bringing european innovation



smet

FOR MORE INFORMATION CONTACT: **Smet Building Products Ltd**

93A Belfast Road | Newry | BT34 1QH | Northern Ireland

T: +44 (0) 28 3026 6833 | F: +44 (0) 28 3026 7619

E: info@smetbuildingproducts.com

www.smetbuildingproducts.com or www.smet.ie



The information, and, in particular, the recommendations relating to the application and end-use of SMET distributed products, are given in good faith based on SMET's current knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance with the manufacturer's recommendations. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The user of the product must test the product's suitability for the intended application and purpose. The manufacturer reserves the right to change the properties of its products. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local Product Data Sheet for the product concerned, copies of which will be supplied on request.