

Product data sheet

# CASUBLANCA DEEP GEL

## Product description

CASUBLANCA DEEP GEL is a water-based special primer without of preservatives for exterior and interior dispersion paints.

Special primer with novel gel structure for optimum roller and spray application. For the stabilisation of substrates and for the reduction of absorbency.

### > Technical data and properties

Colour	Blueish-transparent
Specific weight	1,02 kg/l
Base	Hydrosol pure acrylate
Dilution	Ready to use
Consumption	Approx. 150 ml/m <sup>2</sup> depending on substrate. Exact consumption values for the calculation must be determined on the object.
Application	Painting, rolling
Drying	Can be recoated after approx. 12 hours at 20 °C and 60 % relative humidity. In case of cool, humid air, observe accordingly longer drying times.

### > Logistics and safety instructions

Form of delivery	In 12 l bucket
Storability	CASUBLANCA DEEP GEL should be used within 6 months of the filling date (see additional piping) when stored cool, frost-free and dry in closed containers.
Safety instructions	See safety data sheet GISCODE: BSW 10 obsolete: M-GF01  EU threshold value for this product (Cat. A/h): 30 g/l (2010). This product contains < 1 g/l VOC.

The information, and, in particular, the recommendations relating to the application and end-use of SMET distributed products, are given in good faith based on SMET's current knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance with the manufacturer's recommendations. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The user of the product must test the product's suitability for the intended application and purpose. The manufacturer reserves the right to change the properties of its products. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local Product Data Sheet for the product concerned, copies of which will be supplied on request.

**For further information,  
please contact:**

REMONDIS Production  
GmbH  
Department CASUL  
COLOURS  
Brunnenstr. 138  
44536 Lünen  
Deutschland  
T +49 2306 106-589  
F +49 2306 106-228  
info@casul-colours.de  
casul-colours.de

A company of the  
REMONDIS group

### Substrates

The substrate must be clean, dry and load-bearing. The guidelines of VOB, part C, DIN 18 363, paragraphs 2 and 3 must be observed. Non-adhesive old coats must be completely removed. Ideally applicable for applying on weakly chalking substrates as well as on mechanically abraded substrates.

Sanding or highly absorbent substrates require pre-treatment with CASUBLANCA DEEP PLUS.

### Processing

CASUBLANCA DEEP GEL can be applied with a roller or brush. In most cases, a one-time painting is sufficient. Ready to use.

Stir gently before use and use undiluted.

Processing and drying not at temperatures below + 5 °C

### Important to note

- Avoid eating, drinking and smoking while using the primer.
- Protect skin and eyes during application. After contact with the eye, rinse it thoroughly under running water for a sufficient period of time. In case of noticeable aftereffects, consult an ophthalmologist.
- Application and drying not at temperatures below + 5 °C, based on substrate temperature and ambient temperature.
- The treated components and surfaces must be protected against unfavourable weather conditions (strong solar radiation, wind, driving rain, frost, etc.).
- Stir well before use. Close the container tightly again after use.
- Clean tools with water immediately after use.
- Keep out of the reach of children
- Information on disposal: Disposal must be carried out in accordance with the applicable regulations. Residual quantities can be disposed of when completely dry, such as household waste or building rubble. Only empty containers can be recycled.
- GISCODE: BSW 10 obsolete: M-GF01
- Declaration of ingredients according to VdL guideline "Building paints", hydrosol pure acrylate, water, additives, casul, cellulose derivative

bringing european innovation



FOR MORE INFORMATION CONTACT: Smet Building Products Ltd  
93A Belfast Road | Newry | BT34 1QH | Northern Ireland  
T: +44 (0)28 3026 6833 ROI: +353 (0) 1697 8586  
E: info@smetbuildingproducts.com  
smetbuildingproducts.com or smet.ie

