

CASUBLANCA DEEP PLUS

Product description

CASUBLANCA DEEP PLUS is a solvent-free, diffusible, capillary-compatible plaster hardener without the addition of preservatives for critical substrates such as sanding, porous or highly absorbent plasters as well as for gypsum and gypsum plasterboards and old, chalking paints of dispersion paints, primers for heavy wallpapers and composite boards, also suitable for poorly ventilated rooms.

> Technical data and properties

Colour	Blueish-transparent
Specific weight	1.01 kg/l
Base	Pure acrylic hydrosol
pH-value	ca. 10.5
Dilution	Ready to use and drip-resistant. Normally use undiluted. If necessary, dilute with max. 66 % water.
Consumption	Approx. 150 ml/m ² depending on substrate. Exact consumption values for the calculation must be determined on the object.
Application	Painting, rolling or spraying
Airless spraying	Nozzle 0.007-0.009 inch = 0.18-0.23 mm Pressure: 150 bar, spraying angle: 50°
Drying	Can be recoated after approx. 8 h at 20 ° and 65 % relative humidity. The drying time is extended at low temperatures and/or high humidity.

> Logistics and safety instructions

Form of delivery	In 5 l and 10 l canisters
Storability	CASUBLANCA DEEP Plus should be used within 12 months if stored cool, frost-free and dry in closed containers.
Safety instructions	See safety data sheet GISCODE: BSW 10 obsolete: M-GF01 EU threshold value for this product (Cat. A/h): 30 g/l (2010). This product contains max. 0.4 g/l VOC.

The information, and, in particular, the recommendations relating to the application and end-use of SMET distributed products, are given in good faith based on SMET's current knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance with the manufacturer's recommendations. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The user of the product must test the product's suitability for the intended application and purpose. The manufacturer reserves the right to change the properties of its products. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local Product Data Sheet for the product concerned, copies of which will be supplied on request.

**For further information,
please contact:**

REMONDIS Production GmbH
Department CASUL COLOURS
Brunnenstr. 138
44536 Lünen
Deutschland
T +49 2306 106-589
F +49 2306 106-228
info@casul-colours.de
casul-colours.de

A company of the
REMONDIS group

Substrates

Suitable substrates are stonework, exposed stonework, plaster, concrete, glass fibre fabric, woodchip, non-woven and embossed wallpaper, dispersion, mineral and silicate paints. The substrate must be clean, dry and load-bearing. The guidelines of VOB, Part C, DIN 18 363, Paragraphs 2 and 3 must be observed. Non-adhesive old coats must be completely removed. Pretreat algae and mould chemically and remove all residues. Remove dust, loose plaster parts, old non-sticky coatings and sintered layers. Clean intact old coats. Only begin to coat new, highly alkaline plasters after 4 weeks. Isolate expected breakthroughs based on nicotine or other substances in advance. On chalking old paintwork and highly absorbent mineral surfaces (e.g. plasters, gypsum planks), apply a primer with a water-thinnable deep primer.

Processing

CASUBLANCA DEEP PLUS can be applied with a roller, brush or airless device. In most cases, a one-time painting is sufficient. Ready to use and drip-resistant. Stir gently before use and use undiluted. After drying, the product is fully covering. Too early reworking may lead to the formation of differences in opacity (danger of stripes, especially in the ceiling area.) To avoid streaks coat wet-on-wet in one action. Processing and drying not at temperatures below + 5 °C and/or relative humidity > 60 %. To ensure uniform colour, only use materials with the same batch number and mixing proportions on one surface. Always carry out a test application before use.

Important to note

- Skin and eyes must be protected during processing. After eye contact, the eye should be rinsed thoroughly under plenty of running water. In case of obvious discomfort, consult an ophthalmologist.
- Stir well before use. Close the container tightly again after use.
- Clean tools with water immediately after use.
- Information on disposal: Disposal must be carried out in accordance with the applicable regulations. Residual quantities can be disposed of when completely dry, such as household waste or building rubble. Only empty containers can be recycled.
- The treated components and surfaces must be protected against unfavourable weather conditions (strong solar radiation, wind, driving rain, frost, etc.).
- Declaration of ingredients: water, defoamer, preservative, acrylate dispersion, casul
- No addition of preservatives during the production of the product. Keep out of the reach of children. For spraying use combination filter A2/P2. Avoid eating, drinking and smoking while using the primer. Skin and eyes must be protected during the application. After eye contact, the eyes should be rinsed thoroughly under running water for a sufficiently long time. In case of significant discomfort, consult an ophthalmologist. Do not empty into drains, water or soil. Contains: 1,2-Benzisothiazol-3(2H) -on / 2-Methyl-2H-isothiazol-3-on. May cause allergic reactions. Advice for persons suffering from isothiazole allergy can be obtained at the poison emergency number Berlin: +49 (0)30-30686700.

bringing european innovation



FOR MORE INFORMATION CONTACT: **Smet Building Products Ltd**

93A Belfast Road | Newry | BT34 1QH | Northern Ireland

T: +44 (0) 28 3026 6833 | F: +44 (0) 28 3026 7619

E: info@smetbuildingproducts.com

www.smetbuildingproducts.com or www.smet.ie

